

ACE FILTRATION LTD

TECHNICAL DATA SHEET: AF113

FASTFIX ACCESS DOOR FOR SPIRAL DUCTING

Construction

- Door:** Inner & Outer door comprises galvanised sheet steel pressing complete with stiffening ribs.
- Fixings:** Door sections held together with two conical springs around a plated bolt. Each bolt has a captive, moulded polypropylene hand wheel to compress the springs and bring the two sections together around the duct.
- Gasket:** One joint self adhesive foam gasket.
- Template:** Each door comes with an adhesive template & fitting instructions.

Standard Sizes & Duct Diameters

Door Sizes mm

200 x 80	250 x 150	400 x 300
80 mm Ø	150 mm Ø	400 mm Ø
100 mm Ø	160 mm Ø	450 mm Ø
125 mm Ø	200 mm Ø	500 mm Ø
	250 mm Ø	560 mm Ø
	300 mm Ø	630 mm Ø
	315 mm Ø	710 mm Ø
	355 mm Ø	760 mm Ø
	400 mm Ø	810 mm Ø
	450 mm Ø	915 mm Ø
		1000 mm Ø

Approximate Weights: 200 x 80 0.4 kg
250 x 150 0.7 kg
400 x 300 1.8 kg

Notes: Most sizes available from stock. Doors to suit larger diameters are available. Please contact the Sales Office on 01474 325666